# Stainless Steel Pressure Gauge (160mm Dial)







### Description

A range of high quality, industrial, all Stainless Steel pressure gauges with class 1 accuracy.

This range of pressure gauges has a bottom or back entry ½" BSPP process connection with all 316L Stainless steel wetted parts.

The 160mm dial has a 304 stainless steel case with laminated safety glass, a bayonet type bezel and is supplied dry as standard. With optional Glycerine filled case for applications where vibration exists.

Available in pressure ranges from -1 to 700 bar (-30"Hg to 0-10000 PSI) including vacuum and compound.

The instrument is suitable for use in gaseous and liquid media in most general industrial applications.

#### **Features**

- 160mm Dial
- Accuracy Class 1.0 (EN837-1)
- 1/2 inch BSP Parallel Process Thread
- -1 bar to 700 bar Ranges
- All Stainless Steel Construction
- Optional Glycerine filled

## **Application**

- General Industrial/Plant Construction
- **Chemical and Pharmaceutical Plants**
- Food, Beverage and Dairy



## **Specification**

Product	160mm Pressure Dial Gauge
Accuracy	EN837-1 Class 1.0 (±1.0% FSD)
Connection	½" BSP Parallel
Dial	160mm 304 St/St bayonet type bezel
Pressure Range(s)	-1 to 700 bar
Material	316 St/St wetted parts
Ingress Protection	IP65
Operating Temp	-20 to +60 °C
Window	Laminated safety glass
Part Number	RCH160



For more information visit:

sterlingsensors.co.uk



**Sterling Sensors UK Ltd** 

Fitmec Works : Hawksley Street : Oldham

United Kingdom : OL8 4PQ

**T:** +44 (0) 161 620 0410 **F:** +44 (0) 161 627 0507 **E:** sales@sterlingsensors.co.uk **W:** sterlingsensors.co.uk