

Utility Pressure Gauge (50mm Dial)



Made in the UK 

Description

A reliable and cost effective, general purpose pressure gauge with 50mm dial.

This range of utility pressure gauges is available with bottom or back entry 1/4" BSPP process connection and brass/bronze wetted parts. The unit has a hard wearing black steel case and bezel with a Polycarbonate window.

Available in pressure ranges from Vacuum to 21 bar (300 PSI) with an accuracy of $\pm 2.5\%$ full scale deflection.

The instrument is suitable for use in gaseous and liquid media which are chemically compatible with the brass/copper alloy wetted parts.



Features

- 50mm Dial
- Bottom or Back Entry
- Accuracy Class 2.5 (EN837-1)
- 1/4" BSPT Process Connection
- Vacuum to 21 bar (300 PSI) Ranges

Application

- Pneumatics
- HVAC
- OEMs

Specification

| Product | Utility Pressure Gauge (50mm Dial) |
|-------------------|--------------------------------------|
| Accuracy | EN837-1 Class 2.5 ($\pm 2.5\%$ FSD) |
| Connection | 1/4" BSP Parallel |
| Dial | 50mm |
| Pressure Range(s) | Vacuum to 21 bar (300 PSI) |
| Material | Brass/Bronze wetted parts |
| Window | Polycarbonate |
| Operating Temp | -20°C to 60°C |
| Case | Black Steel case and bezel |
| Part Number | RE501 |

Looking for something different?

Visit our custom made sensors page and have your sensors your way.



For more information visit:

sterlingsensors.co.uk