

Pt100 with Miniature (KSE) Head



Made in the UK 

Description

Resistance temperature detector (Pt100) with 316 Stainless Steel sheath terminated with a miniature (KSE) terminal head.

A 3 wire class B Pt100 detector within a 3.0mm or 6.0mm diameter stainless steel sheath. This rigid stem probe is ideal for general purpose temperature measurement giving the element protection in air or liquid. The RTD is terminated with a screw top IP68 miniature weather-proof head, this head is often used with smaller diameter probes and is ideal for applications where access is restricted or space is limited. It has an M16 cable entry and comes with a ceramic terminal block.



Features

- IP68 weather-proof miniature head
- Ideal where access is restricted
- Pt100 class A or B available
- 316 Stainless Steel

Application

- Test rigs
- Process industries
- Marine and Transport

Specification

Product	Pt100 with Miniature (KSE) Head
Type	Pt100 3 wire
Temp Range	-50 to +250°C
Length	150, 200, 250, 300, 400, 500 & 1000mm
Terminal Head	IP68 weather-proof KSE head
Diameter \varnothing	3.0mm or 6.0mm
Material	316 stainless steel
Accuracy	Class B
Part Number	RFHABM

Looking for a quote?

Our technical sales engineers will discuss your application and provide a quotation.



For more information visit:

sterlingsensors.co.uk



Sterling Sensors UK Ltd

Fitmec Works ∴ Hawksley Street ∴ Oldham
United Kingdom ∴ OL8 4PQ

T: +44 (0) 161 620 0410 F: +44 (0) 161 627 0507 E: sales@sterlingsensors.co.uk W: sterlingsensors.co.uk