

Pt100 with Lemo Connector



Made in the UK 

Description

High accuracy resistance thermometers (Pt100) with integral 1S Lemo connectors.

A range of 4-wire resistance thermometers (RTDs). The Class A Pt100 element is housed in a 3 or 6mm diameter rigid stem 316 stainless steel sheath and is available in standard lengths of 150, 300 or 500mm.

The RTD has a high quality fixed four pole 1S Lemo connector available in male or female options and has a compact design to ensure the best connection integrity and quick interchange of sensors. Matching sockets are available to order (not included).



Specification

Product	Pt100 with Lemo Connector
Type	3 wire Pt100
Temp Range	-50 to +250 °C
Length	150, 300 & 500mm or to order
Diameter Ø	3 or 6mm probe
Diameter Ø	12mm connector
Material	316 stainless steel
Termination	1S Lemo plug or socket
Part Number	RGLEM

Features

- Pt100 4 wire class A
- 316 Stainless Steel
- Lemo plug or socket
- Easily Interchangeable
- High quality

Application

- OEMs
- Automation
- Machinery

Need this sensor calibrated?

Call us for a quote today



For more information visit:

sterlingsensors.co.uk



Sterling Sensors UK Ltd

Fitmec Works ∴ Hawksley Street ∴ Oldham
United Kingdom ∴ OL8 4PQ

T: +44 (0) 161 620 0410 F: +44 (0) 161 627 0507 E: sales@sterlingsensors.co.uk W: sterlingsensors.co.uk