

Bayonet Thermocouple



Made in the UK 

Description

Adjustable bayonet thermocouple for plastic extruders and extrusion machinery.

These spring loaded bayonet thermocouples have an adjustable screw threaded spring 200mm long with a single slot 11.5mm I.D fixing cap to ensure a positive contact within the machine recess. The thermocouple is available in type K or J housed in a 4.7mm (3/16") or 6mm diameter stainless steel tip with a 2 metre glass fibre stainless steel overbraid lead wire.



Features

- Adjustable spring loaded tip
- 11.5mm single slot cap as standard, with optional double slot and 12.5, 15, 16 or 17mm caps available
- For use up to 400 °C
- Complete range of single or double slot adaptors with lengths to suit application

Application


- Plastic extrusion machines
- General purpose machinery

Specification

Product	Bayonet Thermocouple
Type	K or J
Temp Range	-50 to 400°C
Length	2 metres overall
Length 2	200mm spring
Tip Ø	4.7mm (3/16") or 6.0mm
Cap Ø	11.5mm I.D with sing slot
Accuracy	Class 1
Termination	stripped wires or connector
Part Number	TGBAY

We supply editable standard drawings...

to help you specify your required dimensions



For more information visit:

sterlingsensors.co.uk



Sterling Sensors UK Ltd

Fitmec Works ∴ Hawksley Street ∴ Oldham
United Kingdom ∴ OL8 4PQ

T: +44 (0) 161 620 0410 F: +44 (0) 161 627 0507 E: sales@sterlingsensors.co.uk W: sterlingsensors.co.uk