

Tarmac Thermocouple



Made in the UK 

Description

Heavy duty hand held T-Bar thermocouple probe commonly used in Tarmac and aggregate applications.

A robust T-bar thermocouple designed for penetration of semi solids, such as; Tarmac, compost, soil, animal feeds and aggregates up to 300°C.

The rigid stainless steel stem is a heavy duty 11mm diameter with a chisel tip designed for penetration. This sensor is available in lengths of 500mm, 1m, 1.5m or 2m and thermocouple types J or K. It includes a stainless steel handle, 1 metre coiled cable and mini plug for use with hand held indicators.



Specification

Product	Tarmac Thermocouple
Type	Type J or K
Temp Range	-75 to 300°C
Probe Length	500mm, 1m, 1.5m or 2metre standard or to order
Sheath	Stainless Steel
Accuracy	Class 1
Probe Dia	11mm
Handle Length	11mm dia x 150mm
Lead Length	300mm (expands to 1 metre)
Termination	Mini Plug
Part Number	TGTAR

Features

- 11mm Diameter Heavy Duty Design
- Type J or K Thermocouple
- 500mm, 1m, 1.5m or 2 metre lengths
- -75 to 300°C temperature range

Application

- Compost and Soil
- Animal Feed Hotspots
- Tarmac

We also make sensors to drawing, sketch or sample

Click here to find out more.



For more information visit:

sterlingsensors.co.uk



Sterling Sensors UK Ltd

Fitmec Works ∴ Hawksley Street ∴ Oldham
United Kingdom ∴ OL8 4PQ

T: +44 (0) 161 620 0410 F: +44 (0) 161 627 0507 E: sales@sterlingsensors.co.uk W: sterlingsensors.co.uk